



# 60K – 75K Cable Hoists



## H06022K, H07522K

Specifications Model	H06022K ROUSA	H07522K ROUSA
Box Length	22 foot	22 foot
Capacity	60,000 lbs	75,000 lbs
Lift & Reeving Cylinders (Interchangeable)	6" Bore x 79" Stroke x 4" Rod	7" Bore x 79" Stroke x 4" Rod
Frame Material	10" x 4" x 1/2" Rectangular Tubing ASTM A-500 Grade-C w/1/2" x 3" Bar Wear Strips	10" x 4" x 1/2" Rectangular Tubing ASTM A-500 Grade-C w/1/2" x 3" Bar Wear Strips
Cable Sheaves (all 5 interchangeable)	10" x 2.25" CRS Diameter w/Aluminum Bronze Bushings	10" x 2.25" CRS Diameter w/Aluminum Bronze Bushings
Cable	7/8" EXWRC	7/8" EXWRC
Rollers (outside)	4" diameter x 3.75" long CR Steel w/ Aluminum Bronze Bushings	4" diameter x 3.75" long CR Steel with Aluminum Bronze Bushings
Grease Fittings	At All Wear Points	At All Wear Points
Dump Angle	Approximately 50°	Approximately 50°
Front Stops	7/8" Steel Plate	7/8" Steel Plate
Rear Hinge	2.5" CR Diameter Axel	2.5" CR Diameter Axel
Front Container Lock	Automatic, 1 1/2" Diameter Pin CR1018	Automatic, 1 1/2" Diameter Pin CR1018
Rear Hold Down	Strap and Ratchet	Strap and Ratchet
Rear Ground Roller (Quick Change)	8.5" OD x 3/4" Wall x 27" Long Axel	8.5" OD x 3/4" Wall x 27" Long Axel
Bumper	ICC Manual Fold Bumper	ICC Manual Fold Bumper
Hoist Up Alarm	In Cab Buzzer	In Cab Buzzer
Back up Alarm	97 Dec	97 Dec
Hydraulics	Hard Plumbing with 5 Bank Valve	Hard Plumbing with 5 Bank Valve





**Options Chassis Specification's  
RECOMMENDED GVWR**

Front.....	18000 lbs
Rear.....	44000 lbs
Total GVWR.....	62,000 lbs
Frame Height.....	41" - 45"
After Frame.....	59"
Effective CA.....	186"
Clear of Side Obstructions behind Cab.....	34"
Recommended Container Length.....	18' to 22'

**APPROX. WEIGHT MOUNTED**

Front.....	1800 lbs
Rear.....	6900 lbs
Total GVWR.....	8700 lbs

**Tarpers:**

- Pioneer, O'Brian, Roll Rite, Donavan

**Fenders:**

- Steel, Aluminum, or Plastic Fenders

**Other Options:**

- Inside Air Controls Joy stick or 2 levers
- Fire Extinguisher
- 24' Box Capacity 24' Hoist
- Automatic Box Locks
- Auxiliary Hydraulic Power Hookups
- Pusher Type 3rd Axle
- Inside/Outside Rail
- Behind The Cab Oil Tank
- Tool Boxes: 24", 36", 48"
- Container Stops: Fold Up
- Rear Window Screen ----- Cab Guard
- Pintle Hook (Hoist is standard with Pintle Hook Plate Drilled for Pintle Hook)
- 2" Suction Hose
- Rear ½" x 4" Approach Ramps
- LED Lights
- Automatic Air Assist Bumper



**Performance**

	<b>Model 60000</b>	<b>Model 75000</b>
<b>Hydraulic System</b>	40 Gal.Side Mounted Tank	40 Gal.Side Mounted Tank
<b>Filtration</b>	100 Mesh Suction S trainer/10 Micron Return Filter	100 Mesh Suction S trainer/10 Micron Return Filter
<b>Pressure</b>	1900 PSI	1900 PSI
<b>Flow</b>	36 GPM @ 1500 RPM	36 GPM @ 1500 RPM
<b>Hoist Up</b>	24 sec	32 sec
<b>Hoist down</b>	14 sec	23 sec
<b>Cable In</b>	22 sec	25 sec
<b>Cable Out</b>	12 sec	14 sec